


ROUND UNIVERSAL JOINT MULTIPLE SPINDLE HEADS


HEAD STYLE	BASIC MODEL	MAXIMUM SPINDLE PICK-OFFS	CAPACITY IN MILD STEEL	MAXIMUM AREA IN. DIA.	MINIMUM SPINDLE C.D.	MAXIMUM MACHINE SPEED RPM	RATIO DRIVER TO DRIVEN
Rnd	350	5	3/16	3	7/16	1500	1:1
Rnd	500	6	3/8	4 3/4	7/16	1800	1:1
Rnd	700	10	3/8	6 1/2	7/16	1800	1:1
Rnd	850	10	3/8	8 1/4	7/16	1800	1:1
Rnd	875	10	3/8	8 1/4	7/16	1800	1:1
Rnd	950	8	3/8	8 3/4	7/16	950	1:2
Rnd	1200	19	1/2	11 7/8	7/16	1750	1:1



- Close center capacity
- Extremely versatile – maximum flexibility of application
- Operate in any position – upright, inverted or horizontal
- Adapts to any drilling machine – standard adapter caps available to fit most popular drilling machines

RECTANGLE UNIVERSAL JOINT MULTIPLE SPINDLE HEADS

HEAD STYLE	BASIC MODEL	MAXIMUM SPINDLE PICK-OFFS	CAPACITY IN MILD STEEL	MAXIMUM AREA IN. DIA.	MINIMUM SPINDLE C.D.	MAXIMUM MACHINE SPEED RPM	RATIO DRIVER TO DRIVEN
Rect	3-22	15	3/8	3 x 22	1/2	1800	1:1
Rect	4-15	25	3/8	4 x 15	1/2	1800	1:1
Rect	4-24	29	1/2	4 x 24	5/8	1800	1:1
Rect	4-36	46	1/2	4 x 36	1/2	1800	1:1
Rect	8-12	15	3/8-1/2	8 x 12	1/2	1750	1:1



- Rectangular pattern permits adaptation to short throat machines
- Close center capacity
- Extremely versatile – maximum flexibility of application
- Operate in any position – upright, inverted or horizontal