

MULTI-DRILL

MODEL

Adjustable Gear Driven Drill Head

Low Cost . . . extremely efficient and versatile drill heads, excellent for shortrun multiple hole drilling . . . as well as long runs.



The Model 200 Multi-Drill is a versatile and efficient unit designed for close center multiple drilling and tapping operations. Where close centers are not a factor, we recommend a unit in the 400 series. We will adapt the 200 unit to any drill press.

Commander Multi-Drill has on file spindle specifications for most machines. Please furnish us with the make and model number of the machine that our head will be adapted to. (See adaptations page)


In some cases there may be an additional charge for adaptation.


| BASIC HEAD 200 | ITEM # | |
|--|--------|--|
| Basic Unit without Adaptation 3/8 Minimum Center Distance | C70150 | |
| Basic Unit with Adaptation 3/8 Minimum Center Distance | C70151 | |
| Basic Unit without Adaptation 1/2 Minimum Center Distance | C70155 | |
| Basic Unit with Adaptation 1/2 Minimum Center Distance | C7015 | |


| SPECIFICATIONS | |
|--|----------------|
| Maximum Number of Spindles | 2 |
| Maximum Horsepower Transmitted | 1/4 |
| Maximum Torque Transmitted | 14 in./lbs. |
| Maximum Spindle RPM | 2000 |
| Maximum Drill Press RPM | 900 |
| Minimum Center Distance | 3/8 |
| Maximum Drilling Area | 1.96" |
| Ratio (1/2 centers) | 1:2 |
| Ratio (3/8 centers) | 1:2.2 increase |
| Approximate Drill Capacity in mild steel | 1/8 |











| COMMANDER 200 SPINDLE HEAD ASSEMBLIES | | | | |
|--|-----------------|--------------------|----------|--|
| DESCRIPTION | MIN. CENTERS | LENGTH PART NO. | DIM. "E" | |
| 125 COLLET TYPE 1/32 TO 1/8 DIAM. | 1/2 | C74001 | 2-7/16 | |
| 125 BORED TYPE (SPEC. EXACT SIZE MAX. 187) | 1/2 | C74006 | 2-9/16 | |
| 130 COLLET TYPE 1/32 TO 1/8 DIAMETER | 3/8 | C74020 | 2-7/16 | |
| 157 BORED TYPE (SPEC. EXACT SIZE MAX. 157) | 3/8 | C74007 | 1-5/8 | |